

Claims

What is claimed is:

1. An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
 - a support member;
 - a cutting device for cutting the tubular member coupled to the support member; and
 - an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member.
2. The apparatus of claim 1, further comprising:
 - a gripping device for gripping the tubular member coupled to the support member.
3. The apparatus of claim 2, wherein the gripping device comprises a plurality of movable gripping elements.
4. The apparatus of claim 3, wherein the gripping elements are moveable in a radial direction relative to the support member.
5. The apparatus of claim 3, wherein the gripping elements are moveable in an axial direction relative to the support member.
6. The apparatus of claim 3, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.
7. The apparatus of claim 3, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.
8. The apparatus of claim 3, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction relative to the support member.

9. The apparatus of claim 3, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.
10. The apparatus of claim 3, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.
11. The apparatus of claim 3, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.
12. The apparatus of claim 3, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.
13. The apparatus of claim 1, further comprising:
a sealing device for sealing an interface with the tubular member coupled to the support member.
14. The apparatus of claim 13, wherein the sealing device seals an annulus defines between the support member and the tubular member.
15. The apparatus of claim 1, further comprising:

a locking device for locking the position of the tubular member relative to the support member.

16. The apparatus of claim 1, further comprising:
a packer assembly coupled to the support member.

17. The apparatus of claim 16, wherein the packer assembly comprises:
a packer; and
a packer control device for controlling the operation of the packer coupled to the support member.

18. The apparatus of claim 17, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.

19. The apparatus of claim 17, wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.

20. The apparatus of claim 17, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and
wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.

21. The apparatus of claim 1, further comprising:

an actuator for displacing the expansion device relative to the support member.

22. The apparatus of claim 21, wherein the actuator comprises:
a first actuator for pulling the expansion device; and
a second actuator for pushing the expansion device.
23. The apparatus of claim 21, wherein the actuator comprises means for transferring torsional loads between the support member and the expansion device.
24. The apparatus of claim 22, wherein the first and second actuators comprise means for transferring torsional loads between the support member and the expansion device.
25. The apparatus of claim 21, wherein the actuator comprises a plurality of pistons positioned within corresponding piston chambers.
26. The apparatus of claim 1, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.
27. The apparatus of claim 26, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.
28. The apparatus of claim 27, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
29. The apparatus of claim 28, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
30. The apparatus of claim 27, wherein the cutting elements comprise:
a first set of cutting elements; and
a second set of cutting elements;

wherein the first set of cutting elements are interleaved with the second set of cutting elements.

31. The apparatus of claim 30, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.
32. The apparatus of claim 30, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
33. The apparatus of claim 1, wherein the expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
34. The apparatus of claim 33, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
35. The apparatus of claim 34, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
36. The apparatus of claim 35, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
37. The apparatus of claim 34, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
38. The apparatus of claim 37, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.

39. The apparatus of claim 37, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.
40. The apparatus of claim 1, wherein the expansion device comprises an adjustable expansion device.
41. The apparatus of claim 1, wherein the expansion device comprises a plurality of expansion devices.
42. The apparatus of claim 41, wherein at least one of the expansion devices comprises an adjustable expansion device.
43. The apparatus of claim 42, wherein the adjustable expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
44. The apparatus of claim 43, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
45. The apparatus of claim 44, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
46. The apparatus of claim 45, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
47. The apparatus of claim 44, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.

48. The apparatus of claim 47, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.
49. The apparatus of claim 47, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.
50. An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:
a support member;
an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and
an actuator coupled to the support member for displacing the expansion device relative to the support member.
51. The apparatus of claim 50, further comprising:
a cutting device coupled to the support member for cutting the tubular member.
52. The apparatus of claim 51, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.
53. The apparatus of claim 52, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.
54. The apparatus of claim 53, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the tubular member.
55. The apparatus of claim 54, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
56. The apparatus of claim 53, wherein the cutting elements comprise:

a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements.

57. The apparatus of claim 56, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.
58. The apparatus of claim 56, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
59. The apparatus of claim 50, further comprising:
a gripping device for gripping the tubular member coupled to the support member.
60. The apparatus of claim 59, wherein the gripping device comprises a plurality of movable gripping elements.
61. The apparatus of claim 60, wherein the gripping elements are moveable in a radial direction relative to the support member.
62. The apparatus of claim 60, wherein the gripping elements are moveable in an axial direction relative to the support member.
63. The apparatus of claim 60, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.
64. The apparatus of claim 60, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.
65. The apparatus of claim 60, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the

second position, the gripping elements move in a radial direction relative to the support member.

66. The apparatus of claim 60, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.

67. The apparatus of claim 50, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.

68. The apparatus of claim 60, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.

69. The apparatus of claim 60, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.

70. The apparatus of claim 50, further comprising:
a sealing device for sealing an interface with the tubular member coupled to the support member.

71. The apparatus of claim 70, wherein the sealing device seals an annulus defined between the support member and the tubular member.

72. The apparatus of claim 50, further comprising:
a locking device for locking the position of the tubular member relative to the support member.
73. The apparatus of claim 50, further comprising:
a packer assembly coupled to the support member.
74. The apparatus of claim 73, wherein the packer assembly comprises:
a packer; and
a packer control device for controlling the operation of the packer coupled to the support member.
75. The apparatus of claim 74, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.
76. The apparatus of claim 74, wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.
77. The apparatus of claim 74, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and
wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.

78. The apparatus of claim 50, wherein the expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
79. The apparatus of claim 78, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
80. The apparatus of claim 79, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
81. The apparatus of claim 80, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
82. The apparatus of claim 79, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
83. The apparatus of claim 82, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
84. The apparatus of claim 82, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
85. The apparatus of claim 50, wherein the expansion device comprises an adjustable
expansion device.
86. The apparatus of claim 50, wherein the expansion device comprises a plurality of
expansion devices.

87. The apparatus of claim 86, wherein at least one of the expansion devices comprises an adjustable expansion device.
88. The apparatus of claim 87, wherein the adjustable expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
89. The apparatus of claim 88, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
90. The apparatus of claim 89, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
91. The apparatus of claim 90, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
92. The apparatus of claim 89, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
93. The apparatus of claim 92, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
94. The apparatus of claim 92, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
95. An apparatus for radially expanding and plastically deforming an expandable tubular
member, comprising:
a support member;

an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and
a sealing assembly for sealing an annulus defined between the support member and the tubular member.

96. The apparatus of claim 95, further comprising:
a gripping device for gripping the tubular member coupled to the support member.
97. The apparatus of claim 96, wherein the gripping device comprises a plurality of movable gripping elements.
98. The apparatus of claim 97, wherein the gripping elements are moveable in a radial direction relative to the support member.
99. The apparatus of claim 97, wherein the gripping elements are moveable in an axial direction relative to the support member.
100. The apparatus of claim 97, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.
101. The apparatus of claim 97, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.
102. The apparatus of claim 97, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction relative to the support member.
103. The apparatus of claim 97, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do

engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.

104. The apparatus of claim 97, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.

105. The apparatus of claim 97, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.

106. The apparatus of claim 97, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.

107. The apparatus of claim 95, further comprising:
a locking device for locking the position of the tubular member relative to the support member.

108. The apparatus of claim 95, further comprising:
a packer assembly coupled to the support member.

109. The apparatus of claim 108, wherein the packer assembly comprises:
a packer; and
a packer control device for controlling the operation of the packer coupled to the support member.

110. The apparatus of claim 109, wherein the packer comprises:

a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.

111. The apparatus of claim 109, wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.
112. The apparatus of claim 109, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and
wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.
113. The apparatus of claim 95, further comprising:
an actuator for displacing the expansion device relative to the support member.
114. The apparatus of claim 113, wherein the actuator comprises:
a first actuator for pulling the expansion device; and
a second actuator for pushing the expansion device.
115. The apparatus of claim 113, wherein the actuator comprises means for transferring torsional loads between the support member and the expansion device.
116. The apparatus of claim 114, wherein the first and second actuators comprise means for transferring torsional loads between the support member and the expansion device.

117. The apparatus of claim 113, wherein the actuator comprises a plurality of pistons positioned within corresponding piston chambers.
118. The apparatus of claim 95, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.
119. The apparatus of claim 118, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.
120. The apparatus of claim 119, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
121. The apparatus of claim 120, wherein the sensor prevents the cutting elements from
being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
122. The apparatus of claim 119, wherein the cutting elements comprise:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting
elements.
123. The apparatus of claim 122, wherein in the first position, the first set of cutting
elements are not axially aligned with the second set of cutting elements.
124. The apparatus of claim 122, wherein in the second position, the first set of cutting
elements are axially aligned with the second set of cutting elements.
125. The apparatus of claim 95, wherein the expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.

126. The apparatus of claim 125, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
127. The apparatus of claim 126, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
128. The apparatus of claim 127, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
129. The apparatus of claim 126, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
130. The apparatus of claim 129, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
131. The apparatus of claim 129, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
132. The apparatus of claim 95, wherein the expansion device comprises an adjustable
expansion device.
133. The apparatus of claim 95, wherein the expansion device comprises a plurality of
expansion devices.
134. The apparatus of claim 133, wherein at least one of the expansion devices comprises
an adjustable expansion device.

135. The apparatus of claim 134, wherein the adjustable expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
136. The apparatus of claim 135, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
137. The apparatus of claim 136, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
138. The apparatus of claim 137, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
139. The apparatus of claim 136, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
140. The apparatus of claim 139, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
141. The apparatus of claim 139, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
142. An apparatus for radially expanding and plastically deforming an expandable tubular
member, comprising:
a support member;
a first expansion device for radially expanding and plastically deforming the tubular
member coupled to the support member; and
a second expansion device for radially expanding and plastically deforming the

tubular member coupled to the support member.

143. The apparatus of claim 142, further comprising:
a gripping device for gripping the tubular member coupled to the support member.
144. The apparatus of claim 143, wherein the gripping device comprises a plurality of movable gripping elements.
145. The apparatus of claim 144, wherein the gripping elements are moveable in a radial direction relative to the support member.
146. The apparatus of claim 144, wherein the gripping elements are moveable in an axial direction relative to the support member.
147. The apparatus of claim 144, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.
148. The apparatus of claim 144, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.
149. The apparatus of claim 144, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction relative to the support member.
150. The apparatus of claim 144, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.

151. The apparatus of claim 144, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.

152. The apparatus of claim 144, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.

153. The apparatus of claim 144, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.

154. The apparatus of claim 142, further comprising:
a sealing device for sealing an interface with the tubular member coupled to the support member.

155. The apparatus of claim 154, wherein the sealing device seals an annulus defines between the support member and the tubular member.

156. The apparatus of claim 142, further comprising:
a locking device for locking the position of the tubular member relative to the support member.

157. The apparatus of claim 142, further comprising:
a packer assembly coupled to the support member.

158. The apparatus of claim 157, wherein the packer assembly comprises:
a packer; and

a packer control device for controlling the operation of the packer coupled to the support member.

159. The apparatus of claim 158, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.
160. The apparatus of claim 158, wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.
161. The apparatus of claim 158, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and
wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.
162. The apparatus of claim 142, further comprising:
an actuator for displacing the expansion device relative to the support member.
163. The apparatus of claim 162, wherein the actuator comprises:
a first actuator for pulling the expansion device; and
a second actuator for pushing the expansion device.
164. The apparatus of claim 162, wherein the actuator comprises means for transferring torsional loads between the support member and the expansion device.

165. The apparatus of claim 163, wherein the first and second actuators comprise means for transferring torsional loads between the support member and the expansion device.
166. The apparatus of claim 162, wherein the actuator comprises a plurality of pistons positioned within corresponding piston chambers.
167. The apparatus of claim 142, further comprising:
a cutting device for cutting the tubular member coupled to the support member.
168. The apparatus of claim 167, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.
169. The apparatus of claim 168, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.
170. The apparatus of claim 169, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
171. The apparatus of claim 170, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
172. The apparatus of claim 169, wherein the cutting elements comprise:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements.
173. The apparatus of claim 172, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.

174. The apparatus of claim 172, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
175. The apparatus of claim 142, wherein at least one of the first second expansion devices comprise:
a support member; and
a plurality of movable expansion elements coupled to the support member.
176. The apparatus of claim 175, further comprising:
an actuator coupled to the support member for moving the expansion elements between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular member; and
wherein in the second position, the expansion elements engage the tubular member.
177. The apparatus of claim 176, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the tubular member.
178. The apparatus of claim 177, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
179. The apparatus of claim 176, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of expansion elements.
180. The apparatus of claim 179, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.
181. The apparatus of claim 179, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.
182. The apparatus of claim 142, wherein at least one of the first and second expansion

devices comprise a plurality of expansion devices.

183. The apparatus of claim 182, wherein at least one of the first and second expansion device comprise an adjustable expansion device.
184. The apparatus of claim 183, wherein the adjustable expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
185. The apparatus of claim 184, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
186. The apparatus of claim 185, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
187. The apparatus of claim 186, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
188. The apparatus of claim 185, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
189. The apparatus of claim 188, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
190. The apparatus of claim 188, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
191. An apparatus for radially expanding and plastically deforming an expandable tubular

member, comprising:

- a support member;
- an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member; and
- a packer coupled to the support member.

192. The apparatus of claim 191, further comprising:

a gripping device for gripping the tubular member coupled to the support member.

193. The apparatus of claim 192, wherein the gripping device comprises a plurality of movable gripping elements.

194. The apparatus of claim 193, wherein the gripping elements are moveable in a radial direction relative to the support member.

195. The apparatus of claim 193, wherein the gripping elements are moveable in an axial direction relative to the support member.

196. The apparatus of claim 193, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.

197. The apparatus of claim 193, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.

198. The apparatus of claim 193, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction relative to the support member.

199. The apparatus of claim 193, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not

engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.

200. The apparatus of claim 193, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.

201. The apparatus of claim 193, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.

202. The apparatus of claim 193, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.

203. The apparatus of claim 191, further comprising:
a sealing device for sealing an interface with the tubular member coupled to the support member.

204. The apparatus of claim 203, wherein the sealing device seals an annulus defines between the support member and the tubular member.

205. The apparatus of claim 191, further comprising:
a locking device for locking the position of the tubular member relative to the support member.

206. The apparatus of claim 191, wherein the packer assembly comprises:

a packer; and
a packer control device for controlling the operation of the packer coupled to the support member.

207. The apparatus of claim 206, wherein the packer comprises:

a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.

208. The apparatus of claim 206, wherein the packer control device comprises:

a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.

209. The apparatus of claim 206, wherein the packer comprises:

a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and

wherein the packer control device comprises:

a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.

210. The apparatus of claim 191, further comprising:

an actuator for displacing the expansion device relative to the support member.

211. The apparatus of claim 210, wherein the actuator comprises:

a first actuator for pulling the expansion device; and
a second actuator for pushing the expansion device.

214. The apparatus of claim 210, wherein the actuator comprises means for transferring

torsional loads between the support member and the expansion device.

215. The apparatus of claim 211, wherein the first and second actuators comprise means for transferring torsional loads between the support member and the expansion device.

216. The apparatus of claim 210, wherein the actuator comprises a plurality of pistons positioned within corresponding piston chambers.

217. The apparatus of claim 191, further comprising a cutting device coupled to the support member for cutting the tubular member.

218. The apparatus of claim 217, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.

219. The apparatus of claim 218, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.

220. The apparatus of claim 219, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.

221. The apparatus of claim 220, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

222. The apparatus of claim 219, wherein the cutting elements comprise:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements.

223. The apparatus of claim 222, wherein in the first position, the first set of cutting

elements are not axially aligned with the second set of cutting elements.

224. The apparatus of claim 222, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.
225. The apparatus of claim 191, wherein the expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.
226. The apparatus of claim 225, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
227. The apparatus of claim 226, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
228. The apparatus of claim 227, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
229. The apparatus of claim 226, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
230. The apparatus of claim 229, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
231. The apparatus of claim 229, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
232. The apparatus of claim 191, wherein the expansion device comprises an adjustable

expansion device.

233. The apparatus of claim 191, wherein the expansion device comprises a plurality of expansion devices.

234. The apparatus of claim 233, wherein at least one of the expansion devices comprises an adjustable expansion device.

235. The apparatus of claim 234, wherein the adjustable expansion device comprises:
a support member; and
a plurality of movable expansion elements coupled to the support member.

236. The apparatus of claim 235, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.

237. The apparatus of claim 236, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.

238. The apparatus of claim 237, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

239. The apparatus of claim 236, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.

240. The apparatus of claim 239, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.

241. The apparatus of claim 239, wherein in the second position, the first set of expansion

elements are axially aligned with the second set of expansion elements.

242. An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

- a support member;
- a cutting device for cutting the tubular member coupled to the support member;
- a gripping device for gripping the tubular member coupled to the support member;
- a sealing device for sealing an interface with the tubular member coupled to the support member;
- a locking device for locking the position of the tubular member relative to the support member;
- a first adjustable expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
- a second adjustable expansion device for radially expanding and plastically deforming the tubular member coupled to the support member;
- a packer coupled to the support member; and
- an actuator for displacing one or more of the sealing assembly, first and second adjustable expansion devices, and packer relative to the support member.

243. The apparatus of claim 242, wherein the gripping device comprises a plurality of movable gripping elements.

244. The apparatus of claim 243, wherein the gripping elements are moveable in a radial direction relative to the support member.

245. The apparatus of claim 243, wherein the gripping elements are moveable in an axial direction relative to the support member.

246. The apparatus of claim 243, wherein the gripping elements are moveable in a radial and an axial direction relative to the support member.

247. The apparatus of claim 243, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member.

248. The apparatus of claim 243, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction relative to the support member.

249. The apparatus of claim 243, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction relative to the support member.

250. The apparatus of claim 243, wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member.

251. The apparatus of claim 243, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, the gripping elements are biased to remain in the first position.

252. The apparatus of claim 243, wherein the gripping device further comprises:
an actuator for moving the gripping elements from a first position to a second position;
wherein in the first position, the gripping elements do not engage the tubular member;
wherein in the second position, the gripping elements do engage the tubular member; and
wherein the actuator is a fluid powered actuator.

253. The apparatus of claim 242, wherein the sealing device seals an annulus defined between the support member and the tubular member.

254. The apparatus of claim 242, wherein the packer assembly comprises:
a packer; and
a packer control device for controlling the operation of the packer coupled to the support member.
255. The apparatus of claim 254, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member;
and
a sliding sleeve valve movably positioned within the passage of the support member.
256. The apparatus of claim 254, wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the packer.
257. The apparatus of claim 254, wherein the packer comprises:
a support member defining a passage;
a shoe comprising a float valve coupled to an end of the support member;
one or more compressible packer elements movably coupled to the support member; and
a sliding sleeve valve positioned within the passage of the support member;
and
wherein the packer control device comprises:
a support member;
one or more drag blocks releasably coupled to the support member; and
a stinger coupled to the support member for engaging the sliding sleeve valve.
258. The apparatus of claim 242, wherein the actuator comprises:
a first actuator for pulling the expansion device; and
a second actuator for pushing the expansion device.
259. The apparatus of claim 242, wherein the actuator comprises means for transferring torsional loads between the support member and the expansion device.

260. The apparatus of claim 258, wherein the first and second actuators comprise means for transferring torsional loads between the support member and the expansion device.
261. The apparatus of claim 242, wherein the actuator comprises a plurality of pistons positioned within corresponding piston chambers.
262. The apparatus of claim 242, wherein the cutting device comprises:
a support member; and
a plurality of movable cutting elements coupled to the support member.
263. The apparatus of claim 262, further comprising:
an actuator coupled to the support member for moving the cutting elements between
a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.
264. The apparatus of claim 263, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
265. The apparatus of claim 264, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
266. The apparatus of claim 263, wherein the cutting elements comprise:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements.
267. The apparatus of claim 266, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.
268. The apparatus of claim 266, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.

269. The apparatus of claim 242, wherein at least one of the adjustable expansion devices comprise:
a support member; and
a plurality of movable expansion elements coupled to the support member.
270. The apparatus of claim 269, further comprising:
an actuator coupled to the support member for moving the expansion elements
between a first position and a second position;
wherein in the first position, the expansion elements do not engage the tubular
member; and
wherein in the second position, the expansion elements engage the tubular member.
271. The apparatus of claim 270, further comprising:
a sensor coupled to the support member for sensing the internal diameter of the
tubular member.
272. The apparatus of claim 271, wherein the sensor prevents the expansion elements
from being moved to the second position if the internal diameter of the tubular member is
less than a predetermined value.
273. The apparatus of claim 270, wherein the expansion elements comprise:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of
expansion elements.
274. The apparatus of claim 273, wherein in the first position, the first set of expansion
elements are not axially aligned with the second set of expansion elements.
275. The apparatus of claim 273, wherein in the second position, the first set of expansion
elements are axially aligned with the second set of expansion elements.
276. The apparatus of claim 242, wherein at least one of the adjustable expansion devices
comprise a plurality of expansion devices.
277. The apparatus of claim 276, wherein at least one of the adjustable expansion devices

comprise:

- a support member; and
- a plurality of movable expansion elements coupled to the support member.

278. The apparatus of claim 277, further comprising:

- an actuator coupled to the support member for moving the expansion elements between a first position and a second position;
- wherein in the first position, the expansion elements do not engage the tubular member; and
- wherein in the second position, the expansion elements engage the tubular member.

279. The apparatus of claim 278, further comprising:

- a sensor coupled to the support member for sensing the internal diameter of the tubular member.

280. The apparatus of claim 279, wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

281. The apparatus of claim 278, wherein the expansion elements comprise:

- a first set of expansion elements; and
- a second set of expansion elements;
- wherein the first set of expansion elements are interleaved with the second set of expansion elements.

282. The apparatus of claim 281, wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements.

283. The apparatus of claim 281, wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements.

284. An apparatus for cutting a tubular member, comprising:

- a support member; and
- a plurality of movable cutting elements coupled to the support member.

285. The apparatus of claim 284, further comprising:

- an actuator coupled to the support member for moving the cutting elements between

a first position and a second position;
wherein in the first position, the cutting elements do not engage the tubular member;
and
wherein in the second position, the cutting elements engage the tubular member.

286. The apparatus of claim 285, further comprising:

a sensor coupled to the support member for sensing the internal diameter of the
tubular member.

287. The apparatus of claim 286, wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

288. The apparatus of claim 285, wherein the cutting elements comprise:

a first set of cutting elements; and

a second set of cutting elements;

wherein the first set of cutting elements are interleaved with the second set of cutting elements.

289. The apparatus of claim 288, wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements.

290. The apparatus of claim 288, wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements.

291. An apparatus for engaging a tubular member, comprising:

a support member; and

a plurality of movable elements coupled to the support member.

292. The apparatus of claim 291, further comprising:

an actuator coupled to the support member for moving the elements between a first position and a second position;

wherein in the first position, the elements do not engage the tubular member; and

wherein in the second position, the elements engage the tubular member.

293. The apparatus of claim 292, further comprising:

a sensor coupled to the support member for sensing the internal diameter of the

tubular member.

294. The apparatus of claim 293, wherein the sensor prevents the elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.
295. The apparatus of claim 292, wherein the elements comprise:
a first set of elements; and
a second set of elements;
wherein the first set of elements are interleaved with the second set of elements.
296. The apparatus of claim 295, wherein in the first position, the first set of elements are not axially aligned with the second set of elements.
297. The apparatus of claim 295, wherein in the second position, the first set of elements are axially aligned with the second set of elements.
298. An apparatus for gripping a tubular member, comprising:
a plurality of movable gripping elements.
299. The apparatus of claim 298, wherein the gripping elements are moveable in a radial direction.
300. The apparatus of claim 298, wherein the gripping elements are moveable in an axial direction.
301. The apparatus of claim 298, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction.
302. The apparatus of claim 298, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in a radial direction.

303. The apparatus of claim 298, wherein the gripping elements are moveable from a first position to a second position; wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; and wherein, during the movement from the first position to the second position, the gripping elements move in an axial direction.
304. The apparatus of claim 298, wherein, in a first axial direction, the gripping device grips the tubular member; and wherein, in a second axial direction, the gripping device does not grip the tubular member.
305. The apparatus of claim 298, further comprising an actuator for moving the gripping elements.
306. The apparatus of claim 298, wherein the gripping elements comprise:
a plurality of separate and distinct gripping elements.
307. An actuator, comprising:
a tubular housing;
a tubular piston rod movably coupled to and at least partially positioned within the housing;
a plurality of annular piston chambers defined by the tubular housing and the tubular piston rod; and
a plurality of tubular pistons coupled to the tubular piston rod, each tubular piston movably positioned within a corresponding annular piston chamber.
308. The actuator of claim 307, further comprising means for transmitting torsional loads between the tubular housing and the tubular piston rod.
309. An apparatus for controlling a packer, comprising:
a tubular support member;
one or more drag blocks releasably coupled to the tubular support member; and
a tubular stinger coupled to the tubular support member for engaging the packer.
310. The apparatus of claim 309, further comprising a tubular sleeve coupled to the drag blocks.
311. The apparatus of claim 309, wherein the tubular support member comprises one or

more axially aligned teeth for engaging the packer.

312. A packer comprising:

- a support member defining a passage;
- a shoe comprising a float valve coupled to an end of the support member;
- one or more compressible packer elements movably coupled to the support member;
- and
- a sliding sleeve valve movably positioned within the passage of the support member.

313. A method of radially expanding and plastically deforming an expandable tubular member within a borehole having a preexisting wellbore casing, comprising:

- positioning the tubular member within the borehole in overlapping relation to the wellbore casing;
 - radially expanding and plastically deforming a portion of the tubular member to form a bell section; and
 - radially expanding and plastically deforming a portion of the tubular member above the bell section comprising a portion of the tubular member that overlaps with the wellbore casing;
- wherein the inside diameter of the bell section is greater than the inside diameter of the radially expanded and plastically deformed portion of the tubular member above the bell section.

314. The method of claim 313, wherein radially expanding and plastically deforming a portion of the tubular member to form a bell section comprises:

- positioning an adjustable expansion device within the expandable tubular member;
- supporting the expandable tubular member and the adjustable expansion device within the borehole;
- lowering the adjustable expansion device out of the expandable tubular member;
- increasing the outside dimension of the adjustable expansion device; and
- displacing the adjustable expansion device upwardly relative to the expandable tubular member n times to radially expand and plastically deform n portions of the expandable tubular member, wherein n is greater than or equal to 1.

315. A method for forming a mono diameter wellbore casing, comprising:

- positioning an adjustable expansion device within a first expandable tubular member;
- supporting the first expandable tubular member and the adjustable expansion device within a borehole;

lowering the adjustable expansion device out of the first expandable tubular member;
increasing the outside dimension of the adjustable expansion device;
displacing the adjustable expansion device upwardly relative to the first expandable tubular member m times to radially expand and plastically deform m portions of the first expandable tubular member within the borehole;
positioning the adjustable expansion device within a second expandable tubular member;
supporting the second expandable tubular member and the adjustable expansion device within the borehole in overlapping relation to the first expandable tubular member;
lowering the adjustable expansion device out of the second expandable tubular member;
increasing the outside dimension of the adjustable expansion device; and
displacing the adjustable expansion device upwardly relative to the second expandable tubular member n times to radially expand and plastically deform n portions of the second expandable tubular member within the borehole.

316. A method for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:

positioning an adjustable expansion device within the expandable tubular member;
supporting the expandable tubular member and the adjustable expansion device within the borehole;

lowering the adjustable expansion device out of the expandable tubular member;
increasing the outside dimension of the adjustable expansion device;
displacing the adjustable expansion mandrel upwardly relative to the expandable tubular member n times to radially expand and plastically deform n portions of the expandable tubular member within the borehole; and

pressurizing an interior region of the expandable tubular member above the adjustable expansion device during the radial expansion and plastic deformation of the expandable tubular member within the borehole.

317. A method for forming a mono diameter wellbore casing, comprising:

positioning an adjustable expansion device within a first expandable tubular member;
supporting the first expandable tubular member and the adjustable expansion device within a borehole;

lowering the adjustable expansion device out of the first expandable tubular member;
increasing the outside dimension of the adjustable expansion device;

displacing the adjustable expansion device upwardly relative to the first expandable tubular member m times to radially expand and plastically deform m portions of the first expandable tubular member within the borehole;
pressurizing an interior region of the first expandable tubular member above the adjustable expansion device during the radial expansion and plastic deformation of the first expandable tubular member within the borehole;
positioning the adjustable expansion mandrel within a second expandable tubular member;
supporting the second expandable tubular member and the adjustable expansion mandrel within the borehole in overlapping relation to the first expandable tubular member;
lowering the adjustable expansion mandrel out of the second expandable tubular member;
increasing the outside dimension of the adjustable expansion mandrel;
displacing the adjustable expansion mandrel upwardly relative to the second expandable tubular member n times to radially expand and plastically deform n portions of the second expandable tubular member within the borehole; and
pressurizing an interior region of the second expandable tubular member above the adjustable expansion mandrel during the radial expansion and plastic deformation of the second expandable tubular member within the borehole.

318. A method for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:

positioning first and second adjustable expansion devices within the expandable tubular member;
supporting the expandable tubular member and the first and second adjustable expansion devices within the borehole;
lowering the first adjustable expansion device out of the expandable tubular member;
increasing the outside dimension of the first adjustable expansion device;
displacing the first adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform a lower portion of the expandable tubular member;
displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the expandable tubular member;
decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
displacing the second adjustable expansion device upwardly relative to the

expandable tubular member to radially expand and plastically deform portions of the expandable tubular member above the lower portion of the expandable tubular member;

wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.

319. A method for forming a mono diameter wellbore casing, comprising:
- positioning first and second adjustable expansion devices within a first expandable tubular member;
 - supporting the first expandable tubular member and the first and second adjustable expansion devices within a borehole;
 - lowering the first adjustable expansion device out of the first expandable tubular member;
 - increasing the outside dimension of the first adjustable expansion device;
 - displacing the first adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform a lower portion of the first expandable tubular member;
 - displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the first expandable tubular member;
 - decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
 - displacing the second adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform portions of the first expandable tubular member above the lower portion of the expandable tubular member;
 - positioning first and second adjustable expansion devices within a second expandable tubular member;
 - supporting the first expandable tubular member and the first and second adjustable expansion devices within the borehole in overlapping relation to the first expandable tubular member;
 - lowering the first adjustable expansion device out of the second expandable tubular member;
 - increasing the outside dimension of the first adjustable expansion device;
 - displacing the first adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform a lower portion of the second expandable tubular member;
 - displacing the first adjustable expansion device and the second adjustable

- expansion device downwardly relative to the second expandable tubular member;
 - decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
 - and
 - displacing the second adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform portions of the second expandable tubular member above the lower portion of the second expandable tubular member;
 - wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.
320. A method for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
- positioning first and second adjustable expansion devices within the expandable tubular member;
 - supporting the expandable tubular member and the first and second adjustable expansion devices within the borehole;
 - lowering the first adjustable expansion device out of the expandable tubular member;
 - increasing the outside dimension of the first adjustable expansion device;
 - displacing the first adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform a lower portion of the expandable tubular member;
 - pressurizing an interior region of the expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the expandable tubular member by the first adjustable expansion device;
 - displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the expandable tubular member;
 - decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
 - displacing the second adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform portions of the expandable tubular member above the lower portion of the expandable tubular member; and
 - pressurizing an interior region of the expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the expandable tubular member above the lower portion of the expandable

tubular member by the second adjustable expansion device;
wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.

321. A method for forming a mono diameter wellbore casing, comprising:
- positioning first and second adjustable expansion devices within a first expandable tubular member;
 - supporting the first expandable tubular member and the first and second adjustable expansion devices within a borehole;
 - lowering the first adjustable expansion device out of the first expandable tubular member;
 - increasing the outside dimension of the first adjustable expansion device;
 - displacing the first adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform a lower portion of the first expandable tubular member;
 - pressurizing an interior region of the first expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the first expandable tubular member by the first adjustable expansion device;
 - displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the first expandable tubular member;
 - decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
 - displacing the second adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform portions of the first expandable tubular member above the lower portion of the expandable tubular member;
 - pressurizing an interior region of the first expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the first expandable tubular member above the lower portion of the first expandable tubular member by the second adjustable expansion device;
 - positioning first and second adjustable expansion devices within a second expandable tubular member;
 - supporting the first expandable tubular member and the first and second adjustable expansion devices within the borehole in overlapping relation to the first expandable tubular member;
 - lowering the first adjustable expansion device out of the second expandable tubular

member;
increasing the outside dimension of the first adjustable expansion device;
displacing the first adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform a lower portion of the second expandable tubular member;
pressurizing an interior region of the second expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the second expandable tubular member by the first adjustable expansion device;
displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the second expandable tubular member;
decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
displacing the second adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform portions of the second expandable tubular member above the lower portion of the second expandable tubular member; and
pressurizing an interior region of the second expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the second expandable tubular member above the lower portion of the second expandable tubular member by the second adjustable expansion device;
wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.

322. A method for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
supporting the expandable tubular member, an hydraulic actuator, and an adjustable expansion device within the borehole;
increasing the size of the adjustable expansion device; and
displacing the adjustable expansion device upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform a portion of the expandable tubular member.

323. The method of claim 322, further comprising:
reducing the size of the adjustable expansion device after the portion of the expandable tubular member has been radially expanded and plastically

deformed.

324. The method of claim 323, further comprising:
fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member after reducing the size of the adjustable expansion device.
325. The method of claim 324, further comprising:
permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator after fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member.
326. The method of claim 325, further comprising:
injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and a preexisting structure after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
327. The method of claim 325, further comprising:
increasing the size of the adjustable expansion device after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
328. The method of claim 327, further comprising:
displacing the adjustable expansion cone upwardly relative to the expandable tubular member to radially expand and plastically deform another portion of the expandable tubular member.
329. The method of claim 328, further comprising:
if the end of the other portion of the expandable tubular member overlaps with a preexisting structure, then
not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator; and
displacing the adjustable expansion cone upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform the end of the other portion of the expandable tubular member that overlaps with the preexisting structure.

330. A method for forming a mono diameter wellbore casing within a borehole that includes a preexisting wellbore casing, comprising:
supporting the expandable tubular member, an hydraulic actuator, and an adjustable expansion device within the borehole;
increasing the size of the adjustable expansion device;
displacing the adjustable expansion device upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform a portion of the expandable tubular member; and
displacing the adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform the remaining portion of the expandable tubular member and a portion of the preexisting wellbore casing that overlaps with an end of the remaining portion of the expandable tubular member.
331. The method of claim 330, further comprising:
reducing the size of the adjustable expansion device after the portion of the expandable tubular member has been radially expanded and plastically deformed.
332. The method of claim 331, further comprising:
fluidicly sealing the radially expanded and plastically deformed end of the expandable tubular member after reducing the size of the adjustable expansion device.
333. The method of claim 332, further comprising:
permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator after fluidicly sealing the radially expanded and plastically deformed end of the expandable tubular member.
334. The method of claim 333, further comprising:
injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and the borehole after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
335. The method of claim 333, further comprising:
increasing the size of the adjustable expansion device after permitting the position of

the expandable tubular member to float relative to the position of the hydraulic actuator.

336. The method of claim 335, further comprising:
displacing the adjustable expansion cone upwardly relative to the expandable tubular member to radially expand and plastically deform the remaining portion of the expandable tubular member.
337. The method of claim 336, further comprising:
not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator; and
displacing the adjustable expansion cone upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform the end of the remaining portion of the expandable tubular member that overlaps with the preexisting wellbore casing after not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
338. A method of radially expanding and plastically deforming a tubular member, comprising:
positioning the tubular member within a preexisting structure;
radially expanding and plastically deforming a lower portion of the tubular member to form a bell section; and
radially expanding and plastically deforming a portion of the tubular member above the bell section.
339. The method of claim 338, wherein positioning the tubular member within a preexisting structure comprises:
locking the tubular member to an expansion device.
340. The method of claim 339, wherein the outside diameter of the expansion device is less than the inside diameter of the tubular member.
341. The method of claim 339, wherein the expansion device is positioned within the tubular member.
342. The method of claim 339, wherein the expansion device comprises an adjustable

expansion device.

343. The method of claim 342, wherein the adjustable expansion device is adjustable to a plurality of sizes.
344. The method of claim 339, wherein the expansion device comprises a plurality of expansion devices.
345. The method of claim 344, wherein at least one of the expansion devices comprises an adjustable expansion device.
346. The method of claim 345, wherein at least one of the adjustable expansion device is adjustable to a plurality of sizes.
347. The method of claim 338, wherein radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprises:
lowering an expansion device out of an end of the tubular member; and
pulling the expansion device through the end of the tubular member.
348. The method of claim 347, wherein lowering an expansion device out of an end of the tubular member comprises:
lowering the expansion device out of the end of the tubular member; and
adjusting the size of the expansion device.
349. The method of claim 348, wherein the adjustable expansion device is adjustable to a plurality of sizes.
350. The method of claim 348, wherein the expansion device comprises a plurality of adjustable expansion devices.
351. The method of claim 350, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
352. The method of claim 347, wherein pulling the expansion device through the end of the tubular member comprises:
gripping the tubular member; and
pulling an expansion device through an end of the tubular member.

353. The method of claim 352, wherein gripping the tubular member comprises:
permitting axial displacement of the tubular member in a first direction; and
not permitting axial displacement of the tubular member in a second direction.
354. The method of claim 352, wherein pulling the expansion device through the end of the tubular member comprises:
pulling the expansion device through the end of the tubular member using an actuator.
355. The method of claim 338, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:
lowering an expansion device out of an end of the tubular member; and
pulling the expansion device through the end of the tubular member.
356. The method of claim 355, wherein lowering an expansion device out of an end of the tubular member comprises:
lowering the expansion device out of the end of the tubular member; and
adjusting the size of the expansion device.
357. The method of claim 356, wherein the adjustable expansion device is adjustable to a plurality of sizes.
358. The method of claim 356, wherein the expansion device comprises a plurality of adjustable expansion devices.
359. The method of claim 358, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
360. The method of claim 355, wherein pulling the expansion device through the end of the tubular member comprises:
gripping the tubular member; and
pulling an expansion device through an end of the tubular member.
361. The method of claim 360, wherein gripping the tubular member comprises:
permitting axial displacement of the tubular member in a first direction; and
not permitting axial displacement of the tubular member in a second direction.

362. The method of claim 360, wherein pulling the expansion device through the end of the tubular member comprises:
pulling the expansion device through the end of the tubular member using an actuator.
363. The method of claim 355, wherein pulling the expansion device through the end of the tubular member comprises:
pulling the expansion device through the end of the tubular member using fluid pressure.
364. The method of claim 363, wherein pulling the expansion device through the end of the tubular member using fluid pressure comprises:
pressurizing an annulus within the tubular member above the expansion device.
365. The method of claim 338, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:
fluidicly sealing an end of the tubular member; and
pulling the expansion device through the tubular member.
366. The method of claim 365, wherein the expansion device is adjustable.
367. The method of claim 366, wherein the expansion device is adjustable to a plurality of sizes.
368. The method of claim 365, wherein the expansion device comprises a plurality of adjustable expansion devices.
369. The method of claim 368, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
370. The method of claim 365, wherein pulling the expansion device through the end of the tubular member comprises:
gripping the tubular member; and
pulling an expansion device through an end of the tubular member.
371. The method of claim 370, wherein gripping the tubular member comprises:

permitting axial displacement of the tubular member in a first direction; and
not permitting axial displacement of the tubular member in a second direction.

372. The method of claim 370, wherein pulling the expansion device through the end of the tubular member comprises:
pulling the expansion device through the end of the tubular member using an actuator.
373. The method of claim 365, wherein pulling the expansion device through the end of the tubular member comprises:
pulling the expansion device through the end of the tubular member using fluid pressure.
374. The method of claim 373, wherein pulling the expansion device through the end of the tubular member using fluid pressure comprises:
pressurizing an annulus within the tubular member above the expansion device.
375. The method of claim 338, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:
overlapping the portion of the tubular member above the bell section with an end of a preexisting tubular member; and
pulling an expansion device through the overlapping portions of the tubular member and the preexisting tubular member.
376. The method of claim 375, wherein the expansion device is adjustable.
377. The method of claim 376, wherein the expansion device is adjustable to a plurality of sizes.
378. The method of claim 375, wherein the expansion device comprises a plurality of adjustable expansion devices.
379. The method of claim 378, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
380. The method of claim 375, wherein pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

gripping the tubular member; and
pulling the expansion device through the overlapping portions of the tubular member
and the preexisting tubular member.

381. The method of claim 380, wherein gripping the tubular member comprises:
permitting axial displacement of the tubular member in a first direction; and
not permitting axial displacement of the tubular member in a second direction.
382. The method of claim 380, wherein pulling the expansion device through the
overlapping portions of the tubular member and the preexisting tubular member comprises:
pulling the expansion device through the overlapping portions of the tubular member
and the preexisting tubular member using an actuator.
383. The method of claim 375, wherein pulling the expansion device through the
overlapping portions of the tubular member and the preexisting tubular member comprises:
pulling the expansion device through the overlapping portions of the tubular member
and the preexisting tubular member using fluid pressure.
384. The method of claim 383, wherein pulling the expansion device through the
overlapping portions of the tubular member and the preexisting tubular member using fluid
pressure comprises:
pressurizing an annulus within the tubular member above the expansion device.
385. The method of claim 375, further comprising:
cutting an end of the portion of the tubular member that overlaps with the preexisting
tubular member.
386. The method of claim 385, further comprising:
removing the cut off end of the expandable tubular member from the preexisting
structure.
387. The method of claim 338, further comprising:
injecting a hardenable fluidic sealing material into an annulus between the
expandable tubular member and the preexisting structure.
388. The method of claim 338, further comprising:
cutting off an end of the expandable tubular member.

389. The method of claim 388, further comprising:
removing the cut off end of the expandable tubular member from the preexisting structure.
390. A method of radially expanding and plastically deforming a tubular member, comprising:
applying internal pressure to the inside surface of the tubular member at a plurality of discrete location separated from one another.
391. A system for radially expanding and plastically deforming an expandable tubular member within a borehole having a preexisting wellbore casing, comprising:
means for positioning the tubular member within the borehole in overlapping relation to the wellbore casing;
means for radially expanding and plastically deforming a portion of the tubular member to form a bell section; and
means for radially expanding and plastically deforming a portion of the tubular member above the bell section comprising a portion of the tubular member that overlaps with the wellbore casing;
wherein the inside diameter of the bell section is greater than the inside diameter of the radially expanded and plastically deformed portion of the tubular member above the bell section.
392. The system of claim 391, wherein means for radially expanding and plastically deforming a portion of the tubular member to form a bell section comprises:
means for positioning an adjustable expansion device within the expandable tubular member;
means for supporting the expandable tubular member and the adjustable expansion device within the borehole;
means for lowering the adjustable expansion device out of the expandable tubular member;
means for increasing the outside dimension of the adjustable expansion device; and
means for displacing the adjustable expansion device upwardly relative to the expandable tubular member n times to radially expand and plastically deform n portions of the expandable tubular member, wherein n is greater than or equal to 1.

393. A system for forming a mono diameter wellbore casing, comprising:
- means for positioning an adjustable expansion device within a first expandable tubular member;
 - means for supporting the first expandable tubular member and the adjustable expansion device within a borehole;
 - means for lowering the adjustable expansion device out of the first expandable tubular member;
 - means for increasing the outside dimension of the adjustable expansion device;
 - means for displacing the adjustable expansion device upwardly relative to the first expandable tubular member m times to radially expand and plastically deform m portions of the first expandable tubular member within the borehole;
 - means for positioning the adjustable expansion device within a second expandable tubular member;
 - means for supporting the second expandable tubular member and the adjustable expansion device within the borehole in overlapping relation to the first expandable tubular member;
 - means for lowering the adjustable expansion device out of the second expandable tubular member;
 - means for increasing the outside dimension of the adjustable expansion device; and
 - means for displacing the adjustable expansion device upwardly relative to the second expandable tubular member n times to radially expand and plastically deform n portions of the second expandable tubular member within the borehole.
394. A system for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
- means for positioning an adjustable expansion device within the expandable tubular member;
 - means for supporting the expandable tubular member and the adjustable expansion device within the borehole;
 - means for lowering the adjustable expansion device out of the expandable tubular member;
 - means for increasing the outside dimension of the adjustable expansion device;
 - means for displacing the adjustable expansion mandrel upwardly relative to the expandable tubular member n times to radially expand and plastically deform n portions of the expandable tubular member within the borehole; and
 - means for pressurizing an interior region of the expandable tubular member above the adjustable expansion device during the radial expansion and plastic

deformation of the expandable tubular member within the borehole.

395. A system for forming a mono diameter wellbore casing, comprising:
- means for positioning an adjustable expansion device within a first expandable tubular member;
 - means for supporting the first expandable tubular member and the adjustable expansion device within a borehole;
 - means for lowering the adjustable expansion device out of the first expandable tubular member;
 - means for increasing the outside dimension of the adjustable expansion device;
 - means for displacing the adjustable expansion device upwardly relative to the first expandable tubular member m times to radially expand and plastically deform m portions of the first expandable tubular member within the borehole;
 - means for pressurizing an interior region of the first expandable tubular member above the adjustable expansion device during the radial expansion and plastic deformation of the first expandable tubular member within the borehole;
 - means for positioning the adjustable expansion mandrel within a second expandable tubular member;
 - means for supporting the second expandable tubular member and the adjustable expansion mandrel within the borehole in overlapping relation to the first expandable tubular member;
 - means for lowering the adjustable expansion mandrel out of the second expandable tubular member;
 - means for increasing the outside dimension of the adjustable expansion mandrel;
 - means for displacing the adjustable expansion mandrel upwardly relative to the second expandable tubular member n times to radially expand and plastically deform n portions of the second expandable tubular member within the borehole; and
 - means for pressurizing an interior region of the second expandable tubular member above the adjustable expansion mandrel during the radial expansion and plastic deformation of the second expandable tubular member within the borehole.

396. A system for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
- means for positioning first and second adjustable expansion devices within the

expandable tubular member;
means for supporting the expandable tubular member and the first and second adjustable expansion devices within the borehole;
means for lowering the first adjustable expansion device out of the expandable tubular member;
means for increasing the outside dimension of the first adjustable expansion device;
means for displacing the first adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform a lower portion of the expandable tubular member;
means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the expandable tubular member;
means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
means for displacing the second adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform portions of the expandable tubular member above the lower portion of the expandable tubular member;
wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.

397. A system for forming a mono diameter wellbore casing, comprising:
means for positioning first and second adjustable expansion devices within a first expandable tubular member;
means for supporting the first expandable tubular member and the first and second adjustable expansion devices within a borehole;
means for lowering the first adjustable expansion device out of the first expandable tubular member;
means for increasing the outside dimension of the first adjustable expansion device;
displacing the first adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform a lower portion of the first expandable tubular member;
means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the first expandable tubular member;
means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;

- means for displacing the second adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform portions of the first expandable tubular member above the lower portion of the expandable tubular member;
 - means for positioning first and second adjustable expansion devices within a second expandable tubular member;
 - means for supporting the first expandable tubular member and the first and second adjustable expansion devices within the borehole in overlapping relation to the first expandable tubular member;
 - means for lowering the first adjustable expansion device out of the second expandable tubular member;
 - means for increasing the outside dimension of the first adjustable expansion device; displacing the first adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform a lower portion of the second expandable tubular member;
 - means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the second expandable tubular member;
 - means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device; and
 - means for displacing the second adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform portions of the second expandable tubular member above the lower portion of the second expandable tubular member;
 - wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.
398. A system for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
- means for positioning first and second adjustable expansion devices within the expandable tubular member;
 - means for supporting the expandable tubular member and the first and second adjustable expansion devices within the borehole;
 - means for lowering the first adjustable expansion device out of the expandable tubular member;
 - means for increasing the outside dimension of the first adjustable expansion device;

- means for displacing the first adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform a lower portion of the expandable tubular member;
- means for pressurizing an interior region of the expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the expandable tubular member by the first adjustable expansion device;
- means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the expandable tubular member;
- means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
- means for displacing the second adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform portions of the expandable tubular member above the lower portion of the expandable tubular member; and
- means for pressurizing an interior region of the expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the expandable tubular member above the lower portion of the expandable tubular member by the second adjustable expansion device;
- wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.
399. A system for forming a mono diameter wellbore casing, comprising:
- means for positioning first and second adjustable expansion devices within a first expandable tubular member;
- means for supporting the first expandable tubular member and the first and second adjustable expansion devices within a borehole;
- means for lowering the first adjustable expansion device out of the first expandable tubular member;
- means for increasing the outside dimension of the first adjustable expansion device; displacing the first adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform a lower portion of the first expandable tubular member;
- means for pressurizing an interior region of the first expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the first expandable tubular member by the first adjustable

- expansion device;
- means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the first expandable tubular member;
- means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
- means for displacing the second adjustable expansion device upwardly relative to the first expandable tubular member to radially expand and plastically deform portions of the first expandable tubular member above the lower portion of the expandable tubular member;
- means for pressurizing an interior region of the first expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the first expandable tubular member above the lower portion of the first expandable tubular member by the second adjustable expansion device;
- means for positioning first and second adjustable expansion devices within a second expandable tubular member;
- means for supporting the first expandable tubular member and the first and second adjustable expansion devices within the borehole in overlapping relation to the first expandable tubular member;
- means for lowering the first adjustable expansion device out of the second expandable tubular member;
- means for increasing the outside dimension of the first adjustable expansion device;
- means for displacing the first adjustable expansion device upwardly relative to the second expandable tubular member to radially expand and plastically deform a lower portion of the second expandable tubular member;
- means for pressurizing an interior region of the second expandable tubular member above the first adjustable expansion device during the radial expansion of the lower portion of the second expandable tubular member by the first adjustable expansion device;
- means for displacing the first adjustable expansion device and the second adjustable expansion device downwardly relative to the second expandable tubular member;
- means for decreasing the outside dimension of the first adjustable expansion device and increasing the outside dimension of the second adjustable expansion device;
- means for displacing the second adjustable expansion device upwardly relative to the

- second expandable tubular member to radially expand and plastically deform portions of the second expandable tubular member above the lower portion of the second expandable tubular member; and
- means for pressurizing an interior region of the second expandable tubular member above the second adjustable expansion device during the radial expansion of the portions of the second expandable tubular member above the lower portion of the second expandable tubular member by the second adjustable expansion device;
- wherein the outside dimension of the first adjustable expansion device is greater than the outside dimension of the second adjustable expansion device.
400. A system for radially expanding and plastically deforming an expandable tubular member within a borehole, comprising:
- means for supporting the expandable tubular member, an hydraulic actuator, and an adjustable expansion device within the borehole;
- means for increasing the size of the adjustable expansion device; and
- means for displacing the adjustable expansion device upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform a portion of the expandable tubular member.
401. The system of claim 400, further comprising:
- means for reducing the size of the adjustable expansion device after the portion of the expandable tubular member has been radially expanded and plastically deformed.
402. The system of claim 401, further comprising:
- means for fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member after reducing the size of the adjustable expansion device.
403. The system of claim 402, further comprising:
- means for permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator after fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member.
404. The system of claim 403, further comprising:
- means for injecting a hardenable fluidic sealing material into an annulus between the

expandable tubular member and a preexisting structure after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.

405. The system of claim 403, further comprising:

means for increasing the size of the adjustable expansion device after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.

406. The system of claim 405, further comprising:

means for displacing the adjustable expansion cone upwardly relative to the expandable tubular member to radially expand and plastically deform another portion of the expandable tubular member.

407. The system of claim 406, further comprising:

if the end of the other portion of the expandable tubular member overlaps with a preexisting structure, then

means for not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator; and

means for displacing the adjustable expansion cone upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform the end of the other portion of the expandable tubular member that overlaps with the preexisting structure.

408. A system for forming a mono diameter wellbore casing within a borehole that includes a preexisting wellbore casing, comprising:

means for supporting the expandable tubular member, an hydraulic actuator, and an adjustable expansion device within the borehole;

means for increasing the size of the adjustable expansion device;

means for displacing the adjustable expansion device upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform a portion of the expandable tubular member; and

means for displacing the adjustable expansion device upwardly relative to the expandable tubular member to radially expand and plastically deform the remaining portion of the expandable tubular member and a portion of the

preexisting wellbore casing that overlaps with an end of the remaining portion of the expandable tubular member.

409. The system of claim 408, further comprising:
means for reducing the size of the adjustable expansion device after the portion of the expandable tubular member has been radially expanded and plastically deformed.
410. The system of claim 409, further comprising:
means for fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member after reducing the size of the adjustable expansion device.
411. The system of claim 410, further comprising:
means for permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator after fluidically sealing the radially expanded and plastically deformed end of the expandable tubular member.
412. The system of claim 411, further comprising:
means for injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and the borehole after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
413. The system of claim 411, further comprising:
means for increasing the size of the adjustable expansion device after permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.
414. The system of claim 413, further comprising:
means for displacing the adjustable expansion cone upwardly relative to the expandable tubular member to radially expand and plastically deform the remaining portion of the expandable tubular member.
415. The system of claim 414, further comprising:
means for not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator; and

means for displacing the adjustable expansion cone upwardly relative to the expandable tubular member using the hydraulic actuator to radially expand and plastically deform the end of the remaining portion of the expandable tubular member that overlaps with the preexisting wellbore casing after not permitting the position of the expandable tubular member to float relative to the position of the hydraulic actuator.

416. A system for radially expanding and plastically deforming a tubular member, comprising:

means for positioning the tubular member within a preexisting structure;

means for radially expanding and plastically deforming a lower portion of the tubular member to form a bell section; and

means for radially expanding and plastically deforming a portion of the tubular member above the bell section.

417. The system of claim 416, wherein means for positioning the tubular member within a preexisting structure comprises:

means for locking the tubular member to an expansion device.

418. The system of claim 417, wherein the outside diameter of the expansion device is less than the inside diameter of the tubular member.

419. The system of claim 417, wherein the expansion device is positioned within the tubular member.

420. The system of claim 417, wherein the expansion device comprises an adjustable expansion device.

421. The system of claim 420, wherein the adjustable expansion device is adjustable to a plurality of sizes.

422. The system of claim 417, wherein the expansion device comprises a plurality of expansion devices.

423. The system of claim 422, wherein at least one of the expansion devices comprises an adjustable expansion device.

424. The system of claim 423, wherein at least one of the adjustable expansion device is adjustable to a plurality of sizes.
425. The system of claim 416, wherein means for radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprises:
means for lowering an expansion device out of an end of the tubular member; and
means for pulling the expansion device through the end of the tubular member.
426. The system of claim 425, wherein means for lowering an expansion device out of an end of the tubular member comprises:
means for lowering the expansion device out of the end of the tubular member; and
means for adjusting the size of the expansion device.
427. The system of claim 426, wherein the adjustable expansion device is adjustable to a plurality of sizes.
428. The system of claim 426, wherein the expansion device comprises a plurality of adjustable expansion devices.
429. The system of claim 428, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
430. The system of claim 425, wherein means for pulling the expansion device through the end of the tubular member comprises:
means for gripping the tubular member; and
means for pulling an expansion device through an end of the tubular member.
431. The system of claim 430, wherein means for gripping the tubular member comprises:
means for permitting axial displacement of the tubular member in a first direction; and
means for not permitting axial displacement of the tubular member in a second direction.
432. The system of claim 430, wherein means for pulling the expansion device through the end of the tubular member comprises:
means for pulling the expansion device through the end of the tubular member using an actuator.

433. The system of claim 416, wherein means for radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:
means for lowering an expansion device out of an end of the tubular member; and
means for pulling the expansion device through the end of the tubular member.
434. The system of claim 433, wherein means for lowering an expansion device out of an end of the tubular member comprises:
means for lowering the expansion device out of the end of the tubular member; and
means for adjusting the size of the expansion device.
435. The system of claim 434, wherein the adjustable expansion device is adjustable to a plurality of sizes.
436. The system of claim 434, wherein the expansion device comprises a plurality of adjustable expansion devices.
437. The system of claim 436, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.
438. The system of claim 433, wherein means for pulling the expansion device through the end of the tubular member comprises:
means for gripping the tubular member; and
means for pulling an expansion device through an end of the tubular member.
439. The system of claim 438, wherein means for gripping the tubular member comprises:
means for permitting axial displacement of the tubular member in a first direction; and
means for not permitting axial displacement of the tubular member in a second direction.
440. The system of claim 438, wherein means for pulling the expansion device through the end of the tubular member comprises:
means for pulling the expansion device through the end of the tubular member using an actuator.
441. The system of claim 433, wherein means for pulling the expansion device through the end of the tubular member comprises:
means for pulling the expansion device through the end of the tubular member using

fluid pressure.

442. The system of claim 441, wherein means for pulling the expansion device through the end of the tubular member using fluid pressure comprises:

means for pressurizing an annulus within the tubular member above the expansion device.

443. The system of claim 416, wherein means for radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

means for fluidically sealing an end of the tubular member; and

means for pulling the expansion device through the tubular member.

444. The system of claim 443, wherein the expansion device is adjustable.

445. The system of claim 444, wherein the expansion device is adjustable to a plurality of sizes.

446. The system of claim 443, wherein the expansion device comprises a plurality of adjustable expansion devices.

447. The system of claim 446, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

448. The system of claim 443, wherein means for pulling the expansion device through the end of the tubular member comprises:

means for gripping the tubular member; and

means for pulling an expansion device through an end of the tubular member.

449. The system of claim 448, wherein means for gripping the tubular member comprises:
means for permitting axial displacement of the tubular member in a first direction; and
means for not permitting axial displacement of the tubular member in a second direction.

450. The system of claim 448, wherein means for pulling the expansion device through the end of the tubular member comprises:

means for pulling the expansion device through the end of the tubular member using an actuator.

451. The system of claim 443, wherein means for pulling the expansion device through the end of the tubular member comprises:

means for pulling the expansion device through the end of the tubular member using fluid pressure.

452. The system of claim 451, wherein means for pulling the expansion device through the end of the tubular member using fluid pressure comprises:

means for pressurizing an annulus within the tubular member above the expansion device.

453. The system of claim 416, wherein means for radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

means for overlapping the portion of the tubular member above the bell section with an end of a preexisting tubular member; and

means for pulling an expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

454. The system of claim 453, wherein the expansion device is adjustable.

455. The system of claim 454, wherein the expansion device is adjustable to a plurality of sizes.

456. The system of claim 453, wherein the expansion device comprises a plurality of adjustable expansion devices.

457. The system of claim 456, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

458. The system of claim 453, wherein means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

means for gripping the tubular member; and

means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

459. The system of claim 458, wherein means for gripping the tubular member comprises:

means for permitting axial displacement of the tubular member in a first direction; and
means for not permitting axial displacement of the tubular member in a second
direction.

460. The system of claim 458, wherein means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using an actuator.

461. The system of claim 453, wherein means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure.

462. The system of claim 461, wherein means for pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure comprises:

means for pressurizing an annulus within the tubular member above the expansion device.

463. The system of claim 453, further comprising:

means for cutting an end of the portion of the tubular member that overlaps with the preexisting tubular member.

464. The system of claim 463, further comprising:

means for removing the cut off end of the expandable tubular member from the preexisting structure.

465. The system of claim 416, further comprising:

means for injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and the preexisting structure.

466. The system of claim 416, further comprising:

means for cutting off an end of the expandable tubular member.

467. The system of claim 466, further comprising:
means for removing the cut off end of the expandable tubular member from the preexisting structure.
468. A system of radially expanding and plastically deforming a tubular member, comprising:
a support member; and
means for applying internal pressure to the inside surface of the tubular member at a plurality of discrete location separated from one another coupled to the support member.
469. A method of cutting a tubular member, comprising:
positioning a plurality of cutting elements within the tubular member; and
bringing the cutting elements into engagement with the tubular member.
470. The method of claim 469, wherein the cutting elements comprise:
a first group of cutting elements; and
a second group of cutting elements;
wherein the first group of cutting elements are interleaved with the second group of cutting elements.
471. The method of claim 469, wherein bringing the cutting elements into engagement with the tubular member comprises:
bringing the cutting elements into axial alignment.
472. The method of claim 471, wherein bringing the cutting elements into engagement with the tubular member further comprises:
pivoting the cutting elements.
473. The method of claim 471, wherein bringing the cutting elements into engagement with the tubular member further comprises:
translating the cutting elements.
474. The method of claim 471, wherein bringing the cutting elements into engagement with the tubular member further comprises:
pivoting the cutting elements; and
translating the cutting elements.

475. The method of claim 469, wherein bringing the cutting elements into engagement with the tubular member comprises:
rotating the cutting elements about a common axis.
476. The method of claim 469, wherein bringing the cutting elements into engagement with the tubular member comprises:
pivoting the cutting elements about corresponding axes;
translating the cutting elements; and
rotating the cutting elements about a common axis.
477. The method of claim 469, further comprising:
preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value.
478. The method of claim 477, wherein preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value comprises:
sensing the inside diameter of the tubular member.
479. A method of gripping a tubular member, comprising:
positioning a plurality of gripping elements within the tubular member; and
bringing the gripping elements into engagement with the tubular member.
480. The method of claim 479, wherein bringing the gripping elements into engagement with the tubular member comprises:
displacing the gripping elements in an axial direction; and
displacing the gripping elements in a radial direction.
481. The method of claim 479, further comprising:
biasing the gripping elements against engagement with the tubular member.
482. A method of operating an actuator, comprising:
pressurizing a plurality of pressure chambers.
483. The method of claim 482, further comprising:

transmitting torsional loads.

484. A method of injecting a hardenable fluidic sealing material into an annulus between a tubular member and a preexisting structure, comprising:
positioning the tubular member into the preexisting structure;
sealing off an end of the tubular member;
operating a valve within the end of the tubular member; and
injecting a hardenable fluidic sealing material through the valve into the annulus between the tubular member and the preexisting structure.
485. A system for cutting a tubular member, comprising:
means for positioning a plurality of cutting elements within the tubular member; and
means for bringing the cutting elements into engagement with the tubular member.
486. The system of claim 485, wherein the cutting elements comprise:
a first group of cutting elements; and
a second group of cutting elements;
wherein the first group of cutting elements are interleaved with the second group of cutting elements.
487. The system of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member comprises:
means for bringing the cutting elements into axial alignment.
488. The system of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member further comprises:
means for pivoting the cutting elements.
489. The system of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member further comprises:
means for translating the cutting elements.
490. The system of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member further comprises:
means for pivoting the cutting elements; and
means for translating the cutting elements.

491. The method of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member comprises:
means for rotating the cutting elements about a common axis.
492. The system of claim 485, wherein means for bringing the cutting elements into engagement with the tubular member comprises:
means for pivoting the cutting elements about corresponding axes;
means for translating the cutting elements; and
means for rotating the cutting elements about a common axis.
493. The system of claim 485, further comprising:
means for preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value.
494. The system of claim 493, wherein means for preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value comprises:
means for sensing the inside diameter of the tubular member.
495. A system for gripping a tubular member, comprising:
means for positioning a plurality of gripping elements within the tubular member; and
means for bringing the gripping elements into engagement with the tubular member.
496. The system of claim 495, wherein means for bringing the gripping elements into engagement with the tubular member comprises:
means for displacing the gripping elements in an axial direction; and
means for displacing the gripping elements in a radial direction.
497. The system of claim 495, further comprising:
means for biasing the gripping elements against engagement with the tubular member.
498. An actuator system, comprising:
a support member; and
means for pressurizing a plurality of pressure chambers coupled to the support member.

499. The system of claim 498, further comprising:
means for transmitting torsional loads.
500. A system for injecting a hardenable fluidic sealing material into an annulus between a tubular member and a preexisting structure, comprising:
means for positioning the tubular member into the preexisting structure;
means for sealing off an end of the tubular member;
means for operating a valve within the end of the tubular member; and
means for injecting a hardenable fluidic sealing material through the valve into the annulus between the tubular member and the preexisting structure.
501. A method of engaging a tubular member, comprising:
positioning a plurality of elements within the tubular member; and
bringing the elements into engagement with the tubular member.
502. The method of claim 501, wherein the elements comprise:
a first group of elements; and
a second group of elements;
wherein the first group of elements are interleaved with the second group of elements.
503. The method of claim 501, wherein bringing the elements into engagement with the tubular member comprises:
bringing the elements into axial alignment.
504. The method of claim 501, wherein bringing the elements into engagement with the tubular member further comprises:
pivoting the elements.
505. The method of claim 501, wherein bringing the elements into engagement with the tubular member further comprises:
translating the elements.
506. The method of claim 501, wherein bringing the elements into engagement with the tubular member further comprises:
pivoting the elements; and

translating the elements.

507. The method of claim 501, wherein bringing the elements into engagement with the tubular member comprises:

rotating the elements about a common axis.

508. The method of claim 501, wherein bringing the elements into engagement with the tubular member comprises:

pivoting the elements about corresponding axes;

translating the elements; and

rotating the elements about a common axis.

509. The method of claim 501, further comprising:

preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value.

510. The method of claim 509, wherein preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value comprises:

sensing the inside diameter of the tubular member.

511. A system for engaging a tubular member, comprising:

means for positioning a plurality of elements within the tubular member; and

means for bringing the elements into engagement with the tubular member.

512. The system of claim 511, wherein the elements comprise:

a first group of elements; and

a second group of elements;

wherein the first group of elements are interleaved with the second group of elements.

513. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member comprises:

means for bringing the elements into axial alignment.

514. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member further comprises:

means for pivoting the elements.

515. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member further comprises:

means for translating the elements.

516. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member further comprises:

means for pivoting the elements; and

means for translating the elements.

517. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member comprises:

means for rotating the elements about a common axis.

518. The system of claim 511, wherein means for bringing the elements into engagement with the tubular member comprises:

means for pivoting the elements about corresponding axes;

means for translating the elements; and

means for rotating the elements about a common axis.

519. The system of claim 511, further comprising:

means for preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value.

520. The system of claim 519, wherein means for preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value comprises:

means for sensing the inside diameter of the tubular member.

521. A packer module for a packer assembly, comprising:

a support member;

one or more compressible packer sealing elements coupled to the support member;

one or more packer compressing elements movably coupled to the support member for compressing the compressible packer sealing elements; and

one or more engagement elements movably coupled to the support member for engaging the interior surface of a tubular member;
wherein each of the packer compressing elements comprise a plurality of circumferentially spaced apart packer compressing elements; and
wherein each of the engagement elements comprise a plurality of circumferentially spaced apart packer compressing elements.

522. An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

- a support member;
- a cutting device for cutting the tubular member coupled to the support member comprising:
 - a support member; and
 - a plurality of movable cutting elements coupled to the support member comprising:
 - a first set of cutting elements; and
 - a second set of cutting elements;
 - wherein the first set of cutting elements are interleaved with the second set of cutting elements;
- an actuator coupled to the support member for moving the cutting elements between a first position and a second position; and
- a sensor coupled to the support member for sensing the internal diameter of the tubular member;
- wherein in the first position, the cutting elements do not engage the tubular member;
- wherein in the second position, the cutting elements engage the tubular member;
- wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements;
- wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements; and
- wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value;
- an expansion device for radially expanding and plastically deforming the tubular member coupled to the support member comprising:
 - one or more adjustable expansion devices, each adjustable expansion device

comprising:

a support member;

a plurality of movable expansion elements coupled to the support member comprising:

a first set of expansion elements; and

a second set of expansion elements;

wherein the first set of expansion elements are interleaved with the second set of expansion elements;

an actuator coupled to the support member for moving the expansion elements between a first position and a second position; and

a sensor coupled to the support member for sensing the internal diameter of the tubular member;

wherein in the first position, the expansion elements do not engage the tubular member;

wherein in the second position, the expansion elements engage the tubular member;

wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements;

wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements; and

wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value;

a gripping device for gripping the tubular member coupled to the support member comprising:

a plurality of radially and axially movable gripping elements; and

a fluid powered actuator coupled to the gripping elements for moving the gripping elements between first and second positions;

wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member, and wherein, the gripping elements are biased to remain in the first position; and

wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular

member is displaced in a second axial direction, the gripping device does not grip the tubular member; and

a sealing device for sealing an interface with the tubular member coupled to the support member;

wherein the sealing device seals an annulus defined between the support member and the tubular member;

a locking device for locking the position of the tubular member relative to the support member;

a packer assembly coupled to the support member comprising:

- a packer comprising:
 - a support member defining a passage;
 - a shoe comprising a float valve coupled to an end of the support member;
 - one or more compressible packer elements movably coupled to the support member; and
 - a sliding sleeve valve movably positioned within the passage of the support member; and
- a packer control device for controlling the operation of the packer coupled to the support member comprising:
 - a support member;
 - one or more drag blocks releasably coupled to the support member;
 - and
 - a stinger coupled to the support member for engaging the packer; and

an actuator for displacing the expansion device relative to the support member comprising:

- a first actuator for pulling the expansion device;
- a second actuator for pushing the expansion device; and
- means for transferring torsional loads between the support member and the expansion device;

wherein at least one of the first and second actuators comprises a plurality of pistons positioned within corresponding piston chambers.

523. An apparatus for radially expanding and plastically deforming an expandable tubular member, comprising:

- a support member;
- a cutting device for cutting the tubular member coupled to the support member comprising:

a support member; and
a plurality of movable cutting elements coupled to the support member comprising:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements;
an actuator coupled to the support member for moving the cutting elements between a first position and a second position; and
a sensor coupled to the support member for sensing the internal diameter of the tubular member;
wherein in the first position, the cutting elements do not engage the tubular member;
wherein in the second position, the cutting elements engage the tubular member;
wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements;
wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements; and
wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value;
a first adjustable expansion device for radially expanding and plastically deforming the tubular member coupled to the support member comprising:
one or more adjustable expansion devices, each adjustable expansion device comprising:
a support member;
a plurality of movable expansion elements coupled to the support member comprising:
a first set of expansion elements; and
a second set of expansion elements;
wherein the first set of expansion elements are interleaved with the second set of expansion elements;
an actuator coupled to the support member for moving the expansion elements between a first position and a second position; and
a sensor coupled to the support member for sensing the internal diameter of the tubular member;

wherein in the first position, the expansion elements do not engage the tubular member;

wherein in the second position, the expansion elements engage the tubular member;

wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements;

wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements; and

wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value;

a second adjustable expansion device for radially expanding and plastically deforming the tubular member coupled to the support member comprising:

one or more adjustable expansion devices, each adjustable expansion device comprising:

- a support member;
- a plurality of movable expansion elements coupled to the support member comprising:
 - a first set of expansion elements; and
 - a second set of expansion elements;
- wherein the first set of expansion elements are interleaved with the second set of expansion elements;

an actuator coupled to the support member for moving the expansion elements between a first position and a second position; and

a sensor coupled to the support member for sensing the internal diameter of the tubular member;

wherein in the first position, the expansion elements do not engage the tubular member;

wherein in the second position, the expansion elements engage the tubular member;

wherein in the first position, the first set of expansion elements are not axially aligned with the second set of expansion elements;

wherein in the second position, the first set of expansion elements are axially aligned with the second set of expansion elements; and

wherein the sensor prevents the expansion elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value;

- a gripping device for gripping the tubular member coupled to the support member comprising:
 - a plurality of radially and axially movable gripping elements; and
 - a fluid powered actuator coupled to the gripping elements for moving the gripping elements between first and second positions;
- wherein in the first position, the gripping elements do not engage the tubular member; wherein in the second position, the gripping elements do engage the tubular member; wherein, during the movement from the first position to the second position, the gripping elements move in a radial and an axial direction relative to the support member, and wherein, the gripping elements are biased to remain in the first position; and
- wherein, if the tubular member is displaced in a first axial direction, the gripping device grips the tubular member; and wherein, if the tubular member is displaced in a second axial direction, the gripping device does not grip the tubular member; and
- a sealing device for sealing an interface with the tubular member coupled to the support member;
 - wherein the sealing device seals an annulus defined between the support member and the tubular member;
- a locking device for locking the position of the tubular member relative to the support member;
- a packer assembly coupled to the support member comprising:
 - a packer comprising:
 - a support member defining a passage;
 - a shoe comprising a float valve coupled to an end of the support member;
 - one or more compressible packer elements movably coupled to the support member; and
 - a sliding sleeve valve movably positioned within the passage of the support member; and
 - a packer control device for controlling the operation of the packer coupled to the support member comprising:
 - a support member;
 - one or more drag blocks releasably coupled to the support member;
 - and
 - a stinger coupled to the support member for engaging the packer; and

an actuator for displacing the first and second adjustable expansion devices relative to the support member comprising:
a first actuator for pulling the first and second expansion device;
a second actuator for pushing the first and second expansion devices; and
means for transferring torsional loads between the support member and the first and second adjustable expansion devices;
wherein at least one of the first and second actuators comprises a plurality of pistons positioned within corresponding piston chambers.

524. An apparatus for cutting a tubular member, comprising:
a support member; and
a plurality of movable cutting elements coupled to the support member comprising:
a first set of cutting elements; and
a second set of cutting elements;
wherein the first set of cutting elements are interleaved with the second set of cutting elements;
an actuator coupled to the support member for moving the cutting elements between a first position and a second position; and
a sensor coupled to the support member for sensing the internal diameter of the tubular member;
wherein in the first position, the cutting elements do not engage the tubular member;
wherein in the second position, the cutting elements engage the tubular member;
wherein in the first position, the first set of cutting elements are not axially aligned with the second set of cutting elements;
wherein in the second position, the first set of cutting elements are axially aligned with the second set of cutting elements; and
wherein the sensor prevents the cutting elements from being moved to the second position if the internal diameter of the tubular member is less than a predetermined value.

525. An apparatus for engaging a tubular member, comprising:
a support member; and

a plurality of movable elements coupled to the support member comprising:
a first set of elements; and
a second set of elements;
wherein the first set of elements are interleaved with the second set of elements;
an actuator coupled to the support member for moving the elements between
a first position and a second position; and
a sensor coupled to the support member for sensing the internal diameter of
the tubular member;
wherein in the first position, the elements do not engage the tubular member;
wherein in the second position, the elements engage the tubular member;
wherein in the first position, the first set of elements are not axially aligned
with the second set of elements;
wherein in the second position, the first set of elements are axially aligned
with the second set of elements; and
wherein the sensor prevents the elements from being moved to the second
position if the internal diameter of the tubular member is less than a
predetermined value.

526. An apparatus for gripping an interior surface of a tubular member, comprising:
a plurality of spaced apart radially and axially movable gripping elements; and
a fluid powered actuator coupled to the gripping elements for moving the
gripping elements between first and second positions;
wherein in the first position, the gripping elements do not engage the tubular
member; wherein in the second position, the gripping elements do
engage the tubular member; wherein, during the movement from the
first position to the second position, the gripping elements move in a
radial and an axial direction relative to the support member, and
wherein, the gripping elements are biased to remain in the first
position; and
wherein, if the tubular member is displaced in a first axial direction, the
gripping device grips the tubular member; and wherein, if the tubular
member is displaced in a second axial direction, the gripping device
does not grip the tubular member.

527. A method of radially expanding and plastically deforming a tubular member,
comprising:

positioning the tubular member within a preexisting structure comprising a preexisting tubular member;

positioning one or more adjustable expansion devices within the tubular member;

locking the tubular member to the one or more adjustable expansion devices;

radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprising:

- lowering one or more of the adjustable expansion devices out of an end of the tubular member;
- adjusting the size of one or more of the adjustable expansion devices; and
- pulling one or more of the adjustable expansion devices through the end of the tubular member comprising gripping the tubular member comprising:
 - permitting axial displacement of the tubular member in a first direction; and
 - not permitting axial displacement of the tubular member in a second direction; and
- pulling one or more of the adjustable expansion devices through an end of the tubular member;

radially expanding and plastically deforming a portion of the tubular member above the bell section comprising:

- lowering one or more of the adjustable expansion devices out of an end of the tubular member;
- adjusting the size of one or more of the adjustable expansion devices; and
- pulling one or more of the adjustable expansion devices through the end of the tubular member comprising gripping the tubular member comprising:
 - permitting axial displacement of the tubular member in a first direction; and
 - not permitting axial displacement of the tubular member in a second direction; and
- pulling one or more of the adjustable expansion devices through an end of the tubular member comprising:
 - pressurizing an annulus defined within the tubular member;
 - and
 - pulling one or more of the adjustable expansion devices through an end of the tubular member using the pressurized annulus;

cutting an end of the portion of the tubular member that overlaps with the preexisting tubular member; and
removing the cut off end of the expandable tubular member from the preexisting structure.

528. A method of radially expanding and plastically deforming a tubular member, comprising:
simultaneously applying internal pressure to the inside surface of the tubular member at a plurality of discrete locations separated from one another.

529. A system for radially expanding and plastically deforming a tubular member, comprising:
a support member; and
means for simultaneously applying internal pressure to the inside surface of the tubular member at a plurality of discrete locations separated from one another.

530. A system for radially expanding and plastically deforming a tubular member, comprising:
means for positioning the tubular member within a preexisting structure comprising a preexisting tubular member;
means for positioning one or more adjustable expansion devices within the tubular member;
means for locking the tubular member to the one or more adjustable expansion devices;
means for radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprising:
means for lowering one or more of the adjustable expansion devices out of an end of the tubular member;
means for adjusting the size of one or more of the adjustable expansion devices; and
means for pulling one or more of the adjustable expansion devices through the end of the tubular member comprising:
means for gripping the tubular member comprising:
means for permitting axial displacement of the tubular member in a first direction; and
means for not permitting axial displacement of the tubular

member in a second direction; and
means for pulling one or more of the adjustable expansion devices
through an end of the tubular member;
means for radially expanding and plastically deforming a portion of the tubular
member above the bell section comprising:
means for lowering one or more of the adjustable expansion devices out of an
end of the tubular member;
means for adjusting the size of one or more of the adjustable expansion
devices; and
means for pulling one or more of the adjustable expansion devices through
the end of the tubular member comprising:
means for gripping the tubular member comprising:
means for permitting axial displacement of the tubular member
in a first direction; and
means for not permitting axial displacement of the tubular
member in a second direction; and
means for pulling one or more of the adjustable expansion devices
through an end of the tubular member comprising:
means for pressurizing an annulus defined within the tubular
member; and
means for pulling one or more of the adjustable expansion
devices through an end of the tubular member using
the pressurized annulus;
means for cutting an end of the portion of the tubular member that overlaps with the
preexisting tubular member; and
means for removing the cut off end of the expandable tubular member from the
preexisting structure.

531. A method of cutting a tubular member, comprising:
positioning a plurality of cutting elements within the tubular member;
bringing the cutting elements into axial alignment;
translating the cutting elements;
pivoting the cutting elements;
rotating the cutting elements about a common axis;
bringing the cutting elements into engagement with the tubular member; and

preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value;

wherein the cutting elements comprise:

a first group of cutting elements; and

a second group of cutting elements;

wherein the first group of cutting elements are interleaved with the second group of cutting elements.

532. A method of gripping a tubular member, comprising:

positioning a plurality of spaced apart gripping elements within the tubular member;
and

bringing the gripping elements into engagement with the tubular member comprising:

displacing the gripping elements in an axial direction; and

displacing the gripping elements in a radial direction; and

biasing the gripping elements against engagement with the tubular member.

533. A system for injecting a hardenable fluidic sealing material into an annulus between a tubular member and a preexisting structure, comprising:

means for positioning the tubular member into the preexisting structure;

means for sealing off an end of the tubular member;

means for operating a valve within the end of the tubular member; and

means for injecting a hardenable fluidic sealing material through the valve into the annulus between the tubular member and the preexisting structure.

534. A system for cutting a tubular member, comprising:

means for positioning a plurality of cutting elements within the tubular member;

means for bringing the cutting elements into axial alignment;

means for translating the cutting elements;

means for pivoting the cutting elements;

means for rotating the cutting elements about a common axis;

means for bringing the cutting elements into engagement with the tubular member;
and

means for preventing the cutting elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value;

wherein the cutting elements comprise:

a first group of cutting elements; and

a second group of cutting elements;

wherein the first group of cutting elements are interleaved with the second group of cutting elements.

535. A system for gripping a tubular member, comprising:

means for positioning a plurality of spaced apart gripping elements within the tubular member; and

means for bringing the gripping elements into engagement with the tubular member comprising:

means for displacing the gripping elements in an axial direction; and

means for displacing the gripping elements in a radial direction; and

means for biasing the gripping elements against engagement with the tubular member.

536. A method of engaging a tubular member, comprising:

positioning a plurality of elements within the tubular member;

bringing the elements into axial alignment;

translating the elements;

pivoting the elements;

rotating the elements about a common axis;

bringing the elements into engagement with the tubular member; and

preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value;

wherein the elements comprise:

a first group of elements; and

a second group of elements;

wherein the first group of elements are interleaved with the second group of elements.

537. A system for engaging a tubular member, comprising:

means for positioning a plurality of elements within the tubular member;

means for bringing the elements into axial alignment;

means for translating the elements;

means for pivoting the elements;

means for rotating the elements about a common axis;

means for bringing the elements into engagement with the tubular member; and
means for preventing the elements from coming into engagement with the tubular member if the inside diameter of the tubular member is less than a predetermined value;

wherein the elements comprise:

a first group of elements; and

a second group of elements;

wherein the first group of elements are interleaved with the second group of elements.

538. The apparatus of claim 15, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
539. The apparatus of claim 538, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
540. The apparatus of claim 539, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
541. The apparatus of claim 540, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
542. The apparatus of claim 539, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
543. The apparatus of claim 542, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
544. The apparatus of claim 15, wherein the locking device comprises:

a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

545. The apparatus of claim 544, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
546. The apparatus of claim 545, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
547. The apparatus of claim 546, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
548. The apparatus of claim 545, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
549. The apparatus of claim 548, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
550. The apparatus of claim 21, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
551. The apparatus of claim 550, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and

one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

552. The apparatus of claim 551, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
553. The apparatus of claim 552, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
554. The apparatus of claim 553, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
555. The apparatus of claim 552, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
556. The apparatus of claim 555, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
557. The apparatus of claim 550, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
558. The apparatus of claim 557, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.

559. The apparatus of claim 558, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
560. The apparatus of claim 559, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
561. The apparatus of claim 558, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
562. The apparatus of claim 561, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
563. The apparatus of claim 22, wherein the second actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
564. The apparatus of claim 563, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
565. The apparatus of claim 564, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
566. The apparatus of claim 565, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
567. The apparatus of claim 566, wherein the actuator comprises:

- a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
568. The apparatus of claim 565, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
569. The apparatus of claim 568, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
570. The apparatus of claim 563, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
571. The apparatus of claim 570, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
572. The apparatus of claim 571, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
573. The apparatus of claim 572, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
574. The apparatus of claim 571, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.

575. The apparatus of claim 574, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
576. The apparatus of claim 50, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
577. The apparatus of claim 576, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
578. The apparatus of claim 577, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
579. The apparatus of claim 578, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
580. The apparatus of claim 579, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
581. The apparatus of claim 578, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
582. The apparatus of claim 581, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
583. The apparatus of claim 576, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;

- a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
- a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
584. The apparatus of claim 583, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
585. The apparatus of claim 584, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
586. The apparatus of claim 585, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
587. The apparatus of claim 584, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
588. The apparatus of claim 587, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
589. The apparatus of claim 72, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
590. The apparatus of claim 589, wherein the locking device further comprises:

a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.

591. The apparatus of claim 590, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
592. The apparatus of claim 591, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
593. The apparatus of claim 590, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
594. The apparatus of claim 593, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
595. The apparatus of claim 72, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
596. The apparatus of claim 595, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
597. The apparatus of claim 596, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.

598. The apparatus of claim 597, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
599. The apparatus of claim 596, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
600. The apparatus of claim 599, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
601. The apparatus of claim 107, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
602. The apparatus of claim 601, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
603. The apparatus of claim 602, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
604. The apparatus of claim 603, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
605. The apparatus of claim 602, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
606. The apparatus of claim 605, wherein the sensor comprises:

- a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
607. The apparatus of claim 107, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
608. The apparatus of claim 607, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
609. The apparatus of claim 608, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
610. The apparatus of claim 609, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
611. The apparatus of claim 608, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
612. The apparatus of claim 611, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
613. The apparatus of claim 113, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.

614. The apparatus of claim 613, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
615. The apparatus of claim 614, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
616. The apparatus of claim 615, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
617. The apparatus of claim 616, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
618. The apparatus of claim 615, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
619. The apparatus of claim 618, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
620. The apparatus of claim 613, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
621. The apparatus of claim 620, wherein the locking device further comprises:

a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.

622. The apparatus of claim 621, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
623. The apparatus of claim 622, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
624. The apparatus of claim 621, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
625. The apparatus of claim 624, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
626. The apparatus of claim 114, wherein the second actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
627. The apparatus of claim 626, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
628. The apparatus of claim 627, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
629. The apparatus of claim 628, wherein the locking device further comprises:

an actuator for displacing the locking element retainer relative to the locking elements.

630. The apparatus of claim 629, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
631. The apparatus of claim 628, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
632. The apparatus of claim 631, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
633. The apparatus of claim 626, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
634. The apparatus of claim 633, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
635. The apparatus of claim 634, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
636. The apparatus of claim 635, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.

637. The apparatus of claim 634, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
638. The apparatus of claim 637, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
639. The apparatus of claim 156, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
640. The apparatus of claim 639, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
641. The apparatus of claim 640, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
642. The apparatus of claim 641, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
643. The apparatus of claim 640, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
644. The apparatus of claim 643, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
645. The apparatus of claim 156, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;

a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

646. The apparatus of claim 645, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
647. The apparatus of claim 646, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
648. The apparatus of claim 647, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
649. The apparatus of claim 646, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
650. The apparatus of claim 649, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
651. The apparatus of claim 162, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
652. The apparatus of claim 651, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and

- one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
653. The apparatus of claim 652, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
654. The apparatus of claim 653, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
655. The apparatus of claim 654, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
656. The apparatus of claim 653, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
657. The apparatus of claim 656, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
658. The apparatus of claim 651, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
659. The apparatus of claim 658, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.

660. The apparatus of claim 659, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
661. The apparatus of claim 660, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
662. The apparatus of claim 659, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
663. The apparatus of claim 662, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
664. The apparatus of claim 163, wherein the second actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
665. The apparatus of claim 664, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
666. The apparatus of claim 665, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
667. The apparatus of claim 666, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
668. The apparatus of claim 667, wherein the actuator comprises:

a fluid powered actuator for displacing the locking element retainer relative to the locking elements.

669. The apparatus of claim 666, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if
a sensed operating condition exceeds a predetermined value.
670. The apparatus of claim 669, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking
elements if a sensed operating pressure exceeds a predetermined value.
671. The apparatus of claim 664, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing
that extend into corresponding openings of the housing for engaging an
interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding
locking elements out of engagement with the interior surface of the
expandable tubular member.
672. The apparatus of claim 671, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for
retaining the locking elements in engagement with the interior surface of the
expandable tubular member.
673. The apparatus of claim 672, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative
to the locking elements.
674. The apparatus of claim 673, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the
locking elements.
675. The apparatus of claim 672, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element
retainer relative to the locking elements if a sensed operating condition
exceeds a predetermined value.

676. The apparatus of claim 675, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
677. The apparatus of claim 205, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
678. The apparatus of claim 677, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
679. The apparatus of claim 678, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
680. The apparatus of claim 679, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
681. The apparatus of claim 678, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
682. The apparatus of claim 681, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
683. The apparatus of claim 205, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and

a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.

684. The apparatus of claim 683, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
685. The apparatus of claim 684, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
686. The apparatus of claim 685, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
687. The apparatus of claim 684, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
688. The apparatus of claim 687, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
689. The apparatus of claim 210, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
690. The apparatus of claim 689, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
691. The apparatus of claim 690, wherein the locking device further comprises:

a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.

692. The apparatus of claim 691, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
693. The apparatus of claim 692, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
694. The apparatus of claim 691, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
695. The apparatus of claim 694, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
696. The apparatus of claim 689, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
697. The apparatus of claim 696, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
698. The apparatus of claim 697, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.

699. The apparatus of claim 698, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
700. The apparatus of claim 697, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
701. The apparatus of claim 700, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
702. The apparatus of claim 211, wherein the second actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
703. The apparatus of claim 702, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
704. The apparatus of claim 703, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
705. The apparatus of claim 704, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
706. The apparatus of claim 705, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
707. The apparatus of claim 704, wherein the locking device further comprises:

a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.

708. The apparatus of claim 707, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
709. The apparatus of claim 702, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
710. The apparatus of claim 709, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
711. The apparatus of claim 710, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
712. The apparatus of claim 711, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
713. The apparatus of claim 710, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
714. The apparatus of claim 713, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.

715. The apparatus of claim 242, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
716. The apparatus of claim 715, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
717. The apparatus of claim 716, wherein the locking device further comprises:
an actuator for displacing the locking element retainer relative to the locking elements.
718. The apparatus of claim 717, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
719. The apparatus of claim 716, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
720. The apparatus of claim 719, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
721. The apparatus of claim 242, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
722. The apparatus of claim 721, wherein the locking device further comprises:

- a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
723. The apparatus of claim 722, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
724. The apparatus of claim 723, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
725. The apparatus of claim 722, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
726. The apparatus of claim 725, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
727. The apparatus of claim 242, wherein the actuator comprises:
a locking device for locking the position of the tubular member relative to the support member.
728. The apparatus of claim 727, wherein the locking device comprises:
one or more locking elements for engaging an interior surface of the expandable tubular member; and
one or more spring elements for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
729. The apparatus of claim 728, wherein the locking device further comprises:
a locking element retainer for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
730. The apparatus of claim 729, wherein the locking device further comprises:

an actuator for displacing the locking element retainer relative to the locking elements.

731. The apparatus of claim 730, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
732. The apparatus of claim 729, wherein the locking device further comprises:
a sensor for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
733. The apparatus of claim 732, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
734. The apparatus of claim 727, wherein the locking device comprises:
a housing defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
735. The apparatus of claim 734, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
736. The apparatus of claim 735, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
737. The apparatus of claim 736, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.

738. The apparatus of claim 735, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
739. The apparatus of claim 738, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
740. An apparatus for locking a tubular member to a support member, comprising:
one or more locking elements coupled to the support member for engaging an interior surface of the expandable tubular member; and
one or more spring elements coupled to the support member for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
741. The apparatus of claim 740, wherein the locking device further comprises:
a locking element retainer coupled to the support member for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
742. The apparatus of claim 741, wherein the locking device further comprises:
an actuator coupled to the support member for displacing the locking element retainer relative to the locking elements.
743. The apparatus of claim 742, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
744. The apparatus of claim 741, wherein the locking device further comprises:
a sensor coupled to the support member for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
745. The apparatus of claim 744, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.

746. The apparatus of claim 740, wherein the locking device comprises:
a housing coupled to the support member defining a plurality of circumferentially spaced apart openings;
a plurality of circumferentially spaced apart locking elements coupled to the housing that extend into corresponding openings of the housing for engaging an interior surface of the expandable tubular member; and
a plurality of spring elements coupled to the housing for biasing corresponding locking elements out of engagement with the interior surface of the expandable tubular member.
747. The apparatus of claim 746, wherein the locking device further comprises:
a locking element retainer releasably coupled to and positioned within the housing for retaining the locking elements in engagement with the interior surface of the expandable tubular member.
748. The apparatus of claim 747, wherein the locking device further comprises:
an actuator coupled to the housing for displacing the locking element retainer relative to the locking elements.
749. The apparatus of claim 748, wherein the actuator comprises:
a fluid powered actuator for displacing the locking element retainer relative to the locking elements.
750. The apparatus of claim 747, wherein the locking device further comprises:
a sensor coupled to the locking element retainer for displacing the locking element retainer relative to the locking elements if a sensed operating condition exceeds a predetermined value.
751. The apparatus of claim 750, wherein the sensor comprises:
a pressure sensor for displacing the locking element retainer relative to the locking elements if a sensed operating pressure exceeds a predetermined value.
752. The method of claim 339, wherein locking the tubular member to an expansion device comprises:
locking the position of the tubular member relative to a support member.

753. The method of claim 752, wherein locking the position of the tubular member relative to a support member comprises:

engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations.

754. The method of claim 753, wherein engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations comprises:

engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members.

755. The method of claim 754, wherein the engagement members are biased out of engagement with the tubular member.

756. The method of claim 752, wherein locking the position of the tubular member relative to a support member comprises:

unlocking the position of the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

757. The method of claim 756, wherein locking the position of the tubular member relative to a support member comprises:

unlocking the position of the tubular member relative to the support member if an operating condition within the tubular member exceeds a predetermined amount.

758. The method of claim 754, wherein locking the position of the tubular member relative to a support member comprises:

releasing the engagement members from engagement with the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

759. The system of claim 339, wherein means for locking the tubular member to an expansion device comprises:

means for locking the position of the tubular member relative to a support member.

760. The system of claim 759, wherein means for locking the position of the tubular member relative to a support member comprises:

means for engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations.

761. The system of claim 760, wherein means for engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations comprises:

means for engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members.

762. The system of claim 761, wherein the engagement members are biased out of engagement with the tubular member.

763. The system of claim 759, wherein means for locking the position of the tubular member relative to a support member comprises:

means for unlocking the position of the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

764. The system of claim 763, wherein means for locking the position of the tubular member relative to a support member comprises:

means for unlocking the position of the tubular member relative to the support member if an operating condition within the tubular member exceeds a predetermined amount.

765. The system of claim 761, wherein means for locking the position of the tubular member relative to a support member comprises:

means for releasing the engagement members from engagement with the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

766. The apparatus of claim 522, wherein the locking device comprises:

a plurality of circumferentially spaced apart locking elements for engaging an interior surface of the tubular member;
a plurality of spring elements for biasing corresponding locking elements out of engagement with the interior surface of the tubular member;
a releasable retaining element for releasably retaining the locking elements in engagement with the interior surface of the tubular member;

an actuator for controllably displacing the retaining element relative to the locking elements; and

a sensor for sensing an operating condition within the tubular member for controllably displacing the retaining element relative to the locking elements.

767. The apparatus of claim 523, wherein the locking device comprises:

a plurality of circumferentially spaced apart locking elements for engaging an interior surface of the tubular member;

a plurality of spring elements for biasing corresponding locking elements out of engagement with the interior surface of the tubular member;

a releasable retaining element for releasably retaining the locking elements in engagement with the interior surface of the tubular member;

an actuator for controllably displacing the retaining element relative to the locking elements; and

a sensor for sensing an operating condition within the tubular member for controllably displacing the retaining element relative to the locking elements.

768. The method of claim 527, wherein locking the tubular member to the one or more adjustable expansion devices comprises:

locking the position of the tubular member relative to a support member.

769. The method of claim 768, wherein locking the position of the tubular member relative to a support member comprises:

engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations.

770. The method of claim 769, wherein engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations comprises:

engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members.

771. The method of claim 770, wherein the engagement members are biased out of engagement with the tubular member.

772. The method of claim 768, wherein locking the position of the tubular member relative to a support member comprises:

unlocking the position of the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

773. The method of claim 772, wherein locking the position of the tubular member relative to a support member comprises:

unlocking the position of the tubular member relative to the support member if an operating condition within the tubular member exceeds a predetermined amount.

774. The method of claim 770, wherein locking the position of the tubular member relative to a support member comprises:

releasing the engagement members from engagement with the tubular member relative to the support member if an operating condition exceeds a predetermined amount.

775. A locking device for locking a tubular member to a support member comprising:
a plurality of circumferentially spaced apart locking elements coupled to the support member for engaging an interior surface of the tubular member;
a plurality of spring elements coupled to the support member for biasing corresponding locking elements out of engagement with the interior surface of the tubular member;
a releasable retaining element releasably coupled to the support member for releasably retaining the locking elements in engagement with the interior surface of the tubular member;
an actuator coupled to the support member for controllably displacing the retaining element relative to the locking elements; and
a sensor coupled to the support member for sensing an operating condition within the tubular member for controllably displacing the retaining element relative to the locking elements.

776. A method of locking a tubular member to a support member comprising:
engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members; and
disengaging the engagement members from the interior surface of the tubular member if an operating condition within the tubular member exceeds a predetermined amount;

wherein the engagement members are biased out of engagement with the tubular member.

777. A system for locking a tubular member to a support member comprising:
means for engaging the interior surface of the tubular member at a plurality of circumferentially spaced apart locations using one or more engagement members; and
means for disengaging the engagement members from the interior surface of the tubular member if an operating condition within the tubular member exceeds a predetermined amount;
wherein the engagement members are biased out of engagement with the tubular member.